

### Product description

Model with mechanical permanent unlocking system in door strike latch. This door strike also includes a reinforced latch bolt spring.

### Overview of Advantages

- Radius keep, FaFix®, adjustable by 3 mm
- Voltage range
- Compatible with current mortise locks
- Compatible with available striking plates
- Symmetrical design. DIN left/right as well as horizontal applicable

### Note

- Also available with standard latch bolt spring
- Also available with black latch bolt spring

### Technical data

|                                |                         |
|--------------------------------|-------------------------|
| Adjustable keeper (FF, FaFix®) | Yes                     |
| Mechanical unlocking (E)       | Yes                     |
| Fail-locked                    | Yes                     |
| Reinforced latch bolt spring   | Yes                     |
| Break-in resistance            | 3750 N                  |
| Height                         | 66 mm                   |
| Width                          | 16 mm                   |
| Depth                          | 25,5 mm                 |
| FaFix® adjustment range        | 3 mm                    |
| Latch bolt engaging depth      | 5,5 mm                  |
| Operating temperature range    | -15 °C to +40 °C        |
| Installation position          | Vertical and horizontal |
| Suitable for fire doors        | No                      |
| Load cycles for in-plant test  | 250000                  |

### Variants that can be ordered

| Order number  | Description                           |
|---------------|---------------------------------------|
| 118EY-----A71 | Without striking plate, 12-24V AC/DC  |
| 118EY-----B71 | Without striking plate, 22-42 V AC/DC |
| 118EY-----D11 | Without strike plate, 6-12 V AC/DC    |

