Standard panic lock N1108

Panic function B

ASSA ABLOY
Opening Solutions



Product description

- The OneSystem panic lock offers the same basic functions as the standard project locks. It offers an innovative design and a range of extended functions: The panic function ensures that the door can always be opened via the handle from the inside. The wide stile version is suitable for both single-leaf and double-leaf doors. For single-leaf panic doors with occasional leaf, the OneSystem espagnolette can be used. The standard panic lock is suitable for universal use and can be fitted with a range of optional monitoring functions. It offers a variety of usage options, as it is available with the panic functions B, C, D, E and P. In combination with the OneSystem panic bars type A and type B, they fulfill the requirements in accordance with EN 1125. The requirements in accordance with EN 179 are fulfilled in combination with various handle Versions.

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 200,000 cycles and 300 kg door weight
- Compliance with EN 179/EN 1125, EN 12209 and suitable for installation in fire doors.
- Panic function inwards/outwards switchable
- Optional: Bus system with integrated monitoring sensors and simplified connection via 5-wire cable
- Latch, reversible between DIN left and right in new design for greater strength and with integrated noise reduction
- Closed lock case
- Optional: Bus System with integrated monitoring function
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Technical data

Backset	55, 60, 65, 80, 100 mm
Distance	72 mm
Face plate shape	Flat face plate: F3 x 20 mm, F3 x 24 mm, R3 x 20 mm, R3 x 24 mm
Material face plate	Stainless steel
DIN direction	DIN L/R (symmetrical face plate), DIN left or DIN right (asymmetrical face plate according to DIN 18251-1)
Bolt throw	20 mm
Handle follower	9 mm
Standards	EN 179, EN 1125, EN12209
Type of cylinder	Profile cylinder
Suitable for fire doors	Yes
Mounting	Standard panic lock
door system	Single-leaf door
Face plate length	235 mm
Monitoring	No
Top locking	No
Self-locking system	No
Door type	Wood/steel wide style
Panic function	D
Functions	mechanical
Screw type	Mortise lock
Brandschutz	Yes
Leaf type	Active door leaf

ASSA ABLOY Sicherheitstechnik GmbH
Bildstockstraße 20 72458 Albstadt albstadt@assaabloy.com
Tel. + 497431 123-0 / www.effeff.de