Standard panic lock N1602

Panic function B

Product description

 OneSystem panic lock N16XX according to EN 179 and EN 1125 for tubular frame doors. Approved for fire barriers according to EN 1634 / product-specific environmental product declaration (EPD) according to EN 15804 with article-specific parameters / tested for 200,000 cycles and 300 kg door weight.

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 200,000 cycles and 300 kg door weight
- Compliance with EN 179/EN 1125, EN 12209
- Small rear backset 15 mm
- Panic function inwards/outwards switchable
- Optional: Bus system with integrated monitoring sensors and simplified connection via 5-wire cable
- Closed lock case
- Latch, reversible between DIN left and right in new design for greater strength and with integrated noise reduction
- Security fittings and oval roses can be screwed on through the lock
- Deadbolt with anti-tampering design
- Optional: Bus System with integrated monitoring function
- Swiss round profile cylinders

Note

• Note: For U-shaped versions, the end caps are included in the scope of supply. Please note that the backset is shortened by 1mm for U-shaped versions. If variants with "no - but prepared" are selected, the face plate is extended by 50 mm to the bottom. This version is designed for doors that may have a monitoring function retrofitted at a later time.

Technical data

Backset	30, 35, 40, 45 mm
Distance	94 mm
Face plate shape	U-shaped face plate: U6 x 24 mm Flat face plate: F3 x 20 mm, F3 x 24 mm, R3 x 20 mm, R3 x 24 mm
Material face plate	Stainless steel
DIN direction	DIN L/R (symmetrical face plate)
Bolt throw	20 mm
Handle follower	9 mm
Standards	EN 179, EN 1125, EN12209
Type of cylinder	Swiss profile cylinder
Suitable for fire doors	Yes
Mounting	Standard panic lock
door system	Double-leaf door
Top locking	No
Monitoring	No
Face plate length	270, 320, 370 mm (depending on version)
Door type	Aluminium/steel profile
Panic function	В
Functions	mechanical
Screw type	Mortise lock
Brandschutz	Yes
Leaf type	Active door leaf